




High lumen down light

Product Description



GLCPro-DL-3K-13W-1000-80D

Power: 13W
 Output current:350mA
 Voltage:34.5-38.1VDC
 CCT:3000, 4000K
 CRI:≥90, PF≤0.9, UGR: <19
 Luminous Flux:1000lm
 Size: Φ210*190*85mm
 Lifetime:L70, 50Kh
 Main texture:ADC12+PMMA
 Beam angle 90° , IP:20/44
 Merrytek DALI 1 Driver for 2 downlights.
 NW:0,45kg, GW:0,84kg



GLCPro-DL-3K-28W-2000-80D

Power: 28W
 Output current:7000mA
 Voltage:35.1-38.7VDC
 CCT:3000, 4000K
 CRI:≥90, PF≤0.9, UGR: <19
 Luminous Flux:2000lm
 Size: Φ230*190*125mm
 Cut-out size: Φ130
 Lifetime:L70, 50Kh
 Main texture:ADC12+PMMA
 Beam angle 90°
 IP:20/44, Merrytek DALI
 NW:0,57kg, GW:1,04kg

Packaging information

GLCPro-DL-3K-28W-2000-80D

Single-Pack: 210x190x85mm,
 Multi-pack: 440x440x125mm,
 4pcs/multi,0,04CBM,

GLCPro-PFS20%-3K-25W

Single-Pack: 328x328x78mm,
 Multi-pack: 480x400x280mm,
 5pcs/multi,0,05CBM,

Driver



220-240Vac,250-700mA, 16-48V DC 123 (L)*79 (W)*23.5 (H)
 1. DALI, Push, 1-10V
 2. Push, 1-10V